

**Precise non-contact  
temperature measurement  
from -50 °C to 975 °C  
(-58 °F to 1787 °F)**



**Features:**

- One of the smallest infrared sensors worldwide with extrem short response time down to 6 ms (90 % signal)
- Fast analog output (0/4–20 mA, 0–5/10 V) with smart real time data processing
- Instant digital 0/10 V output with a response time of 4 ms (50 % signal)
- Continuous process monitoring with an unchoppered sensor system  
Note: Conventional fast pyroelectrical infrared sensors with mechanical chopper see processes only part of the time
- Easy to assemble in multiple arrays for line scanning of small and fast objects (hot spot detection) using a RS485 bus communication
- Rugged up to 120 °C (248 °F) ambient temperature without cooling

**General specifications**

Environmental rating	IP 65 (NEMA-4)
Ambient temperature	-20 °C ... 120 °C (-4 °F ... 248 °F) (sensing head) 0 °C ... 85 °C (32 °F ... 185 °F) (electronics)
Storage temperature	-40 °C ... 120 °C (-40 °F ... 248 °F) (sensing head) -40 °C ... 85 °C (-40 °F ... 185 °F) (electronics)
Relative humidity	10–95%, non condensing
Vibration (sensor)	IEC 68-2-6: 3 G, 11–200 Hz, any axis
Shock (sensor)	IEC 68-2-27: 50 G, 11 ms, any axis
Weight	40 g (1.4 oz) (sensing head) / 420 g (14.8 oz) (electronics)

**Electrical Specifications**

Outputs / analog	0/4–20 mA, 0–5/10 V, thermocouple J, K, alarm
Output / alarm	24 V / 50 mA (open collector)
Outputs / digital	0/10 V (10 mA) optional: relay: 2 x 60 V DC/ 42 V AC; 0.4 A; optically isolated
Digital interface	USB, RS232, RS485, CAN, Profibus DP, Ethernet (optional)
Output impedances	mA max. 500 Ω (with 8–36 V DC) mV min. 100 kΩ load impedance, thermocouple 20 Ω
Inputs	Programmable functional inputs for external emissivity adjustment, ambient temperature compensation, trigger (reset of hold functions)
Cable length	1 m (standard), 3 m, 8 m, 15 m (3.3 ft [standard], 9.8 ft, 26.2 ft, 49.2 ft)
Power Supply	8–36 V DC
Current draw	Max. 100 mA

**Measurement specifications**

Temperature range (scalable via programming keys or software)	-50 °C ... 975 °C (-58 °F ... 1787 °F)
Spectral range	8–14 μm
Optical resolution (90 % energy)	LT15F 15:1 LT25F 25:1
System accuracy (at ambient temp. 23 ±5 °C) (23 ±41 °F)	±1 % or ±2 °C <sup>1), 2)</sup> (±1 % of reading +3.6 °F)
Repeatability (at ambient temp. 23 ±5 °C) (23 ±0.5 °F)	±0.75 % or ±0.75 °C <sup>1), 2)</sup> (±0.75 % of reading +1.4 °F)
Temperature resolution	LT15F 0.2 K <sup>2), 3)</sup> LT25F 0.4 K <sup>2), 3)</sup>
Response time	Analog output (90 %) LT15F 9 ms LT25F 6 ms  Digital output (50 %) LT15F 4 ms LT25F 3 ms
Emissivity/ Gain (adjustable via programming keys or software)	0.100–1.100
Transmissivity/ Gain (adjustable via programming keys or software)	0.100–1.100
Signal processing (parameter adjustable via programming keys or software, respectively)	Peak hold, valley hold, average; extended hold function with threshold and hysteresis
Software	optris® Compact Connect


<sup>1)</sup> Whichever is greater with dynamic noise compression

<sup>2)</sup> At object temperatures ≥20 °C (≥68 °C)


<sup>3)</sup> At time constant 100 ms with smart averaging and T<sub>obj</sub> 25 °C (T<sub>obj</sub> 77 °F)

## Optical specifications


### 15:1 optics




### 15:1 optics with CF-lens



### 25:1 optics




### 25:1 optics with CF-lens




## Dimensions


### Sensing head (standard)



### Electronics



## Compact Connect software



- Software for easy sensor setup and remote controlling, supports multi tasking
- Graphic display for temperature trends and automatic data logging for analysis and documentation with 1 ms response time
- Adjustment of signal processing functions and programming of outputs and functional inputs of the sensor
- Automatic emissivity adjustment
- The software CompactConnect allows to customize the sensor to application needs of the user